Mighty///hi



Standard Features

- All aluminum, steel or aluminum/steel construction
- Solid sides (optional fold-down sides—see below)
- Top and bottom hinged tailgate with spreader and horizontal hold chains
- 9" trapezoidal long sills for ultimate strength and optimum clearance or 4" sub frame and 5" long sills
- Unibody design no subframe/cross members
 cleaner, less chance of corrosion
- All outside edges sloped so product does not catch
- Integrated pull tarp hooks at rear
- Bolt-on hoist mounts and rear hinge for easy mounting
- Integrated safety prop on underbody and front post hoist
- Side board brackets
- See-through bulkhead
- Front manual lever for gate latch with secondary lock
- Standard floor length 9'
- Standard side wall heights 20"
- Standard tail gate height 28"
- Standard width 96" (8')
- Bottom of long sills to top of bulkhead 48" (4')
- LED lights with sealed grote wiring harness to meet DOT requirements





Example of custom design including front post hoist and fold down sides, tool holders, fold down steps and other options.

Options

- Custom lengths and sidewall heights
- Over cab protection
- Underbody or front telescopic pole hoists
- Electric over hydraulic power pack
- Electric tailgate latches
- Pull-out ladders
- Side step on inside of sides (for use when folded down)
- Tool holders
- D-Ring load securement
- Custom design

- Front pull tarp brackets and/or pull tarp
- Safety prop for telescopic pole hoists
- Side steps on inside and outside of sidewalls
- Fold down sides
- Factory installation of lights and labels, tarp and other options available



We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

