

Aluminum Quad Wagon

- 25' long x 8.5' wide x 42" side height
- Base model Aluminum Quad Wagon 15,680 lbs
- Tub-style body with rounded corners and flat floor

Body

- 5083 H321 Aluminum 3/8" floor
- 5052 H321 Aluminum 3/8" wall
- Air trip endgate
- DOT reflective tape
- Formed top rail with sloped ledges
- Plank pockets
- · Solid seam welding
- All hinges greasable or greaseless composite bushings
- Fully integrated sealed beam pre-manufactured wiring/lighting harness
- Michel's flip tarp or gravel tarp in manual crank or electric
- Heavy duty telescopic pinto-pin style cylinders
- Decal package
- Adjustable rear hinge

Frame Specifications

- SAF Holland CBX25 Integrated air suspension and axle
- 25,000 lb. axles and ABS axle comes with unimount wheels
- Sealco CVSS 121 air system
- 16 1/2" x 7" brakes
- High tensile steel
 I-Beam frame
- Haldex Slack Adjusters
- Starblasted, epoxy undercoat, urethane top coat
- Premier drawbar eye assembly
- DOT reflective tape
- RTAC lengths/specs
- Bulldog tongue jack
- 22.5" tires on aluminum rims
- Removable rear impact guard

Available Options

- Lightweight hubs and drums
- Mid-mount hoist stabilizer
- Crank/chain mesh gravel guard tarp
- Crank/chain neoprene gravel guard tarp
- · Electric mesh gravel guard tarp installed
- Electric neoprene gravel guard tarp
- Box liners available
- Turnbuckles and rubber seal for Hazmat gate
- Axle lift systems

Aluminum Quad Wagon









Finding a Better Way

We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

