

SANDSIGET

Proppant Transport Trailer

35 yd³ Aluminum Frac Sand End Dump

Features

- Weight: 10,570 kg
- HT300 -15-001 air ride suspension with dump valve
- IMT 25,000 lb axles with Meritor Wabco Brake system
- Tri-axle design with ABS brakes
- Full aluminum walkway and foldable hand rail system with safety restraint harness
- Two hydraulic stabilizer legs (rear)
- Hydraulic gate controls mounted on both sides of unit
- 45° tilt angle on box
- Mailhot C265-9.25-5 cylinder
- 5" ID steel sand loading lines
- Self-contained Hydraulic pump and reservoir with hydraulic motor
- 100 KSI high tensile all welded manufactured I-Beam frame and aluminum body
- Box sides, roof, front and back walls are ¼" aluminum.
 Sills are ¼" aluminum reinforced with gussets.
- Floor is 1/2" aluminum Grade 5052 H32
- Roof hatches are 22-1/2" x 30-1/2", three for front compartment, two for rear (on two compartment version).
- Air breather on top of unit
- Slope of internal end walls leading to tunnel is 58°.

Available Options

- Polished aluminum body
- 11R24.5 aluminum rims
- Option of 2 or 3 compartments
- · Remote control hydraulic gates
- Additional outriggers
- Toolbox
- Hub odometer











Finding a Better Way

We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

