



StepDeck

Step Deck Trailer

Standard Features

- Fixed Tridem suspension
- 53' overall length
- 8' 6" width
- 21" drop
- 2" x 6" fir decking
- Approximately 14,200 lbs
- L.E.D. lighting

Available Options

- Live roll
- Custom widths built to suit
- Varying deck length from 35' thru 53'
- Tandem axle
- Toolbox
- Ramps
- Pipe stands



STANDARD FEATURES	
Length	53'
Profile	10' Neck, 20" Drop, 41'-1/4" lowbed
Rating	35 Ton, 70,000 lbs
Deck Height	Aprox. 61 1/4" Neck, 42" lowbed
Width	8' 6"
Tare Weight	Aprox. 16,500lbs
Coupler Height	50 1/2"
King Pin	22"
King Pin Plate	5/16"
Flanges	1/2" x 6" 100 ksi yield
Web	100 ksi yield
Front Bolster	Formed Steel; 4 external stake pockets
Rear Bolster	Formed Steel; 3 External stake pockets
Crossmembers	W4x3.2 Steel I-Beams; 16" spacing ahead of axles; 17"/13" spacing at rear suspension
Kneebraces	Steel Tubing 48" spacing
Side Rail	C6x8.2 C- Channel
Rub Rail	1/4"x 3"

Stake Pockets	24" Spacing ahead of suspension; 34"/26" spacing at rear suspension, external, steel
Pipe Spool (winch)	12 per side (60" spacing in suspension area; 48" spacing on lower deck; 44" spacing on upper deck); J-Hooks inbetween
Floor	1.5" Fir
Load Securement	3-Bar Winches, J-Hooks
Mudflaps	Behind rear tires
Paint	Black (other colours available)
Lighting	SAE J560 7 pin plug at front; 4 pin plug at rear, Grote LED Lights and Sealed wiring harness
King Pin	Holland Weld-in
Landing Gear	Holland Mark V; 2 speed
Suspension	Holland Air Ride – 6.5" Ride Height, Quickalign
Axles	25,000lbs; Tridem; 60" spread
ABS Brakes	Meritor Wabco, 2S1M
Brake Lining	16 1/2" x 7"
Hubs	Hub piloted 10 stud Unimount; Oil Lubricated
Brake Drums	Cast

We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

Finding a Better Way
www.cancade.com

Phone: 204-728-4450 Toll-Free 1-800-363-2639 Fax: 204-726-8795
cancade@cancade.com Brandon, Manitoba

