

Steel or Aluminum Tub Design



EXCEPTIONAL PERFORMANCE AND UNMATCHED DESIGN

Basic Body Specifications

- 3/16" high strength floor (1/4" available) with unibody design structure
- 10 ga., 12 ga. or 3/16" high strength sides and ends, heights up to 72" plus extensions (steel or aluminum)
- starblasted, epoxy undercoating and urethane top coats for steel (5 year warranty)
- 4 tailgate designs to choose from (see below)
- all hinges, latches, wear points, pivots are greaseable or composite bushings
- "western style" floor understructure for super clean underside
- no other design cleans out as easily or quickly
- available in steel or aluminum
- fully integrated sealed beam premanufactured wiring/lighting harness
- ladder and climb out rungs
- lower center of gravity and helps center load
- full fender packages
- custom specifications available as per your requirements

See chassis specifications on reverse side.

Call us or a dealer near you for detailed specs. and prices.




Structural integrity and rigidity with no interior obstructions anywhere



Obstruction free hydraulic lift



3 pc. swing-out



Mech. trip shown with beet chute



L.B. air trip



obstruction free interior

Conventional Ag Body Design – Exceeds Your Expectations

MORE PAYLOAD
MORE SAVINGS



Lower Center of Gravity



The Best End Dump Available – Built Better!

Chassis Specifications

- tandem, tridom or custom axle groupings
- spring or air ride suspensions (various options)
- Holland 2 speed landing gear
- high tensile light weight I-beam frame (contoured transitions)
- Sealco CVSS 121 air system
- starblasted, epoxy undercoat, acrylic top coat
- fender kits (various options)
- IMT 22500 lb. axles 77" track
- various axle spacings
- 7 pole electric outlet to front
- optional anti-sway stabilization system
- aluminum or steel wheels
- 2" Holland King pins
- 24–34' lengths
- optional air gauge and blower outlets
- optional lift/self steering axles

Standard Specifications

- 1 pc. side wall and deck rail
- side heights up to 72" x 12 ga.
- 3/16" high strength floor with unibody design structure
- starblasted, epoxy undercoat, urethane top coat for steel (5 yr. warranty)
- 4 tailgate designs to choose from (see reverse side)
- fully integrated sealed beam premanufactured wiring/lighting harness
- front post or underbody hoists
- heavy duty western style tipping sills
- ladder, climb-out rungs
- body design available in steel or aluminum
- custom specifications available as per your requirements
- catwalks



DISTRIBUTED BY: