

CANCADE

COMPANY LIMITED



ALUMINUM GRAVEL BODIES & TRAILERS



17' Tri-Axle Spring Ride Trailer pictured c/w 40" sides, tarp, 11R24.5 tires on aluminum rims weighs 4,720 kgs (10,405 lbs)

Frame Specifications for Stiff Pole Pup Trailers

- Pintle eye to ground distance approximately 22"
- T100 fabricated I beam
- Swivel pintle eye (Premier)
- 10,000 pound jack
- Spicer 22,500 pound axles with disk wheels
- Dust shields, backing plates, auto slacks
- Front post hoist
- 49" or 61" axle spread
- H.T. air or Hutch H9700 (3 leaf) spring suspension
- Meritor CVSS 121 anti-lock (ABS) air brake system
- Seven pole electrical, hydraulic & air lines to hitch
- Sandblasted and epoxy primed and painted
- Sealed beam lighting
- Government safety certified
- Optional axle spreads & wheelbase available

Aluminum Body Specifications

Floor, long sills, rear post, and front - 1/4" - 5083-H321
 Sides - .187", Rear posts, Gate - 1/4" 5083-H321
 Tube and Channel - 6061-T, 8" channel for rear rail and
 4" X 4" x 1/4" gate posts



No crossmembers, no mud or snow hang up



Built in tarp option.



Smooth obstacle free interior for perfect clean out.

Quality Products For Over 60 Years



Brandon, Manitoba

1-800-363-2639 Phone: 204-728-4450 Fax: 204-726-8795
 Email: cancade@cancade.com www.cancade.com



We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

Cancade Company Limited is not responsible for any damage caused by overloading. It is the responsibility of the operator to ensure that the vehicle's GVWR and GAWR are not exceeded.

Distributed by:

SEE OTHER SIDE FOR HARDOX