

Bale Buggy Without Top Loader (Single Tier)

- Capacity: 14 bales (6' diameter)
- GVW: 50,000 lbs or 22,680 kg
- Tractor requirements: 100 HP
- Hydraulic controls requirement: 4 function
- Tires: (4) 385/65R22.5 Super Single tires
- Tire ply / load rating: 18/J (62 mph or 100 km/h)
- Rims: 10 bolt pattern aluminum rims
- Axles: (2) 25,000 lb axles with spring ride, oil bath bearings
- Deck length: 37' (11.3 m)
- Transport width: 12'6" (3.8 m)
- Lighting: Full LED light package including clearance, signal, brake and strobe lights
- Sprockets: 4140 Hardened Chain Drive
- Hitch: Adjustable industrial pintle hitch with rotating socket
- Hoist: 30-ton Cancade 2627 Scissor Hoist
- Options: Quick detach deck to grain or silage body



Bale Buggy With Top Loader (Two Tier)

- Capacity: 20 bales (6' diameter)
- GVW: 50,000 lbs or 22,680 kg
- Tractor requirements: 150 HP
- Hydraulic controls requirement: 6 function
- Tires: (4) 385/65R22.5 Super Single tires
- Tire ply / load rating: 18/J (62 mph or 100 km/h)
- Rims: 10 bolt pattern aluminum rims
- Axles: (2) 25,000 lb axles with spring ride, oil bath bearings
- Deck length: 37' (11.3 m)
- Transport width: 12'6" (3.8 m)
- Lighting: Full LED light package including clearance, signal, brake and strobe lights
- Sprockets: 4140 Hardened Chain Drive
- Hitch: Adjustable industrial pintle hitch with rotating socket
- Hoist: 30-ton Cancade 2627 Scissor Hoist
- Options: Quick detach deck to grain or silage body



Finding a Better Way

We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.