

CANCADE

COMPANY LIMITED

Gravel End Dump

5th Wheel Gravel End Dump Tridem and Tandem

- Available in tandem (29') or tridem (33')
- 3/16" AR200 (100,000 PSI) or 3/16" AR400 (180,000 PSI) yield strength
- Base model weight tridem – 17,149 lbs; base model weight tandem – 14,293 lbs
- Tub-style body with rounded corners and flat floor

Standard Features

- Five-year pro-rated warranty on paint
- Frame is manufactured I-Beam 100,000 PSI
- SAF Holland CBX25 (25,000 lbs) air suspension with auto dump and 15" ride height
- Air trip tailgate – Hazmat-ready; does not include seal and turnbuckles
- 25,000 lb axles, Gunitite auto-slack adjusters, ABS system (one axle) (2S1M)
- 24.5" tires on white steel rims
- Michel's tarp - with 18" tarp hoops
- Telescopic Mailhot 265-8.125-5 hoist
- Adjustable rear hinges for greater overhang for asphalt
- Removable rear impact guard for asphalt
- All hinges greasable or greaseless composite bushings
- Striping graphics package

Available Options

- Lightweight hubs and drums
- Aluminum rims
- Two-speed landing gear
- Mid-mount hoist stabilizer
- Crank/chain mesh gravel guard tarp
- Crank/chain neoprene gravel guard tarp
- Electric mesh gravel guard tarp installed
- Electric neoprene gravel guard tarp
- Box liners available
- Turnbuckles and rubber seal for Hazmat gate
- Axle lift systems



CANCADE

COMPANY LIMITED

Finding a Better Way

We reserve the right to modify, change or revise published specifications without prior notice in order to continually strive for product improvement.

www.cancade.com

Phone: 204-728-4450 Toll-Free 1-800-363-2639 Fax: 204-726-8795
cancade@cancade.com Brandon, Manitoba

